

FLOOR TYPE ELECTRODE OVEN designed for re-baking, conditioning and holding of welding electrode for high quality weld with build in adjustable thermostat controlled with digital temperature display.

- **PID MICRO-PROCESSOR POWER CONTROLLER**
- All ovens are fitted with high temperature door gasket to prevent heat loss.

STAINLESS STEEL BODY

**E200S / E300S
E400S / E600S**



MILD STEEL BODY

**E200M / E300M
E400M / E600M
E1000M**



TIMER OPTION: (0-10hr)



Timer changeover baking temperature to holding temperature controller continuously when time expires. This option saves energy and reduces oxidation to electrode. Holding temperature range from 0 to 300°C.

MODEL	E200M / E200S	E300M / E300S	E400M / E400S	E600M / E600S	E1000M
Capacity (Rod Lght. 450mm)	210 kgs (+/-)	300 kgs (+/-)	400 kgs (+/-)	600 kgs (+/-)	1000 kgs (+/-)
Temperature Range (Average Stabilized)	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F
Input Voltage 50/60Hz	1ph, 220-240VAC	1ph, 220-240VAC	3ph, 380-440VAC	3ph, 380-440VAC	3ph, 380-440VAC
Input Power	2700W	2700W	5300W	6600W	7900W
External Dimension (HxDxW) mm	960x735x620	1115x735x620	1140x755x905	1440x787x910	1700x787x1060
Internal Dimension (HxDxW) mm	505x500x455	650x500x455	650x500x695	950x500x695	1200x500x810
Body Insulation (Ceramic Wool)	75mm	75mm	100mm	100mm	100mm
Weight	86 kgs	96 kgs	168 kgs	217 kgs	242 kgs