

B® Paintstik®

As Markal's most versatile and economic marker, the original B Paintstik solid paint marker combines the durability of paint with the convenience of crayons. The real paint formula has superior marking performance on oily, icy, wet, dry or cold surfaces and is weather and UV-resistant. This Paintstik works on rough, rusty, smooth, or dirty surfaces.

Features & Benefits

- Real paint for long-lasting, highly visible marks
- Superior marking on rough, rusty, or dirty surfaces
- Solid paint marker eliminates replacement tips, sharpening or priming, increasing productivity
- Weather- and UV-resistant for long-lasting marks
- Marking range: -50°F to 150°F (-46°C to 66°C)

Industry Uses

Steel mills and warehouse
Forge and casting foundries
Ship building and repair
Metal fabrication
Tire repair and retreading
Lumber/timber
Construction

Surface Uses

Steel and iron
Pipes and tubes
Rubber and tires
Lumber/timber
Plastic
Glass
Concrete, stone

Details	144 Case	Details	48 Case	B-3/8	144 Case	B-1"	144 Case
Mark Size	11/16" (17mm)	Mark Size	11/16" (17mm)	Mark Size	3/8" (9.5mm)	Mark Size	1" (25.4mm)
80220	☐ White*	80810	☐ White*	80420	☐ White*	80260	☐ White*
80221	☐ Yellow	80811	☐ Yellow	80421	☐ Yellow		
80222	☐ Red	80812	☐ Red				
80223	☐ Black	80813	☐ Black				
80224	☐ Orange	80814	☐ Orange				
80225	☐ Blue	80815	☐ Blue				
80226	☐ Green						
80227	☐ Pink						
80228	☐ Purple						
80229	☐ Brown						
80230	☐ Gray						
80231	☐ Gold						
80232	☐ Aluminum						
80281	☐ Florescent Yellow						



Valve Action® Paint Marker - Low Corrosion Colors

Xylene-free paint reduces user health risks and eliminates California Proposition 65, EPA HAPS and SARA 313 concerns in the U.S.A.
Dura-Nib medium bullet tip resists wear to provide long marking life
Durable metal barrel and clip-cap reduce breakage and store easily in pocket
Marking range: -50°F to 150° (-46°C to 66°C)

Features & Benefits

- Fast-drying paint formula is safe for use on stainless steel and eliminates concerns regarding corrosion, degradation, or pitting.
Confirmed using a typical analysis to contain:
- 200 ppm chlorides and total halogens
 - 250 ppm each low melting point metals
 - 250 ppm sulfur

Industry Uses

Power generation facilities
Oil refineries
Ship building and repair
Aviation and aerospace

Surface Uses

Stainless steel
Alloy and superalloy metals

